1 AN ACT concerning transportation.

Be it enacted by the People of the State of Illinois, represented in the General Assembly:

- Section 5. The Illinois Vehicle Code is amended by changing Sections 15-107 and 15-116 as follows:
- 6 (625 ILCS 5/15-107) (from Ch. 95 1/2, par. 15-107)
- 7 Sec. 15-107. Length of vehicles.
- 8 (a) The maximum length of a single vehicle on any highway 9 of this State may not exceed 42 feet except the following:
- 10 (1) Semitrailers.
- 11 (2) Charter or regulated route buses may be up to 45 12 feet in length, not including energy absorbing bumpers.
- 13 (a-1) A motor home as defined in Section 1-145.01 may be up
- 14 to 45 feet in length, not including energy absorbing bumpers.
- 15 The length limitations described in this subsection (a-1)
- shall be exclusive of energy-absorbing bumpers and rear view
- mirrors.
- 18 (b) The Department shall have the authority to restrict
- 19 vehicle length on its roadways as it deems appropriate.
- 20 (Blank).
- (c) Except as provided in subsections (c-1) and (c-2),
- 22 combinations of vehicles may not exceed a total of 2 vehicles
- 23 except the following:

1	(1) A truck tractor semitrailer may draw one trailer.
2	(2) A truck tractor semitrailer may draw one converter
3	dolly or one semitrailer.
4	(3) A truck tractor semitrailer may draw one vehicle
5	that is defined in Chapter 1 as special mobile equipment,
6	provided the overall dimension does not exceed 60 feet.
7	(4) A truck in transit may draw 3 trucks in transit
8	coupled together by the triple saddlemount method.
9	(5) Recreational vehicles consisting of 3 vehicles,
10	provided the following:
11	(A) The total overall dimension does not exceed 60
12	feet.
13	(B) The towing vehicle is a properly registered
14	vehicle capable of towing another vehicle using a
15	fifth-wheel type assembly.
16	(C) The second vehicle in the combination of
17	vehicles is a recreational vehicle that is towed by a
18	fifth-wheel assembly. This vehicle must be properly
19	registered and must be equipped with brakes,
20	regardless of weight.
21	(D) The third vehicle must be the lightest of the 3
22	vehicles and be a trailer or semitrailer designed or
23	used for transporting a boat, all-terrain vehicle,
24	personal watercraft, or motorcycle.
25	(E) The towed vehicles may be only for the use of

the operator of the towing vehicle.

13

14

15

16

17

18

19

20

21

22

23

24

25

- (F) All vehicles must be properly equipped with 1 2 operating brakes and safety equipment required by this 3 Code, except the additional brake requirement in subdivision (C) of this subparagraph (5). 4 (6) A tow truck in combination with a disabled vehicle or combination of disabled vehicles, provided the towing 6 vehicle: 7 (A) Is specifically designed as a tow truck having 8 9 10 11
 - a gross vehicle weight rating of at least 18,000 pounds and equipped with air brakes, provided that air brakes are required only if the towing vehicle is towing a vehicle, semitrailer, or tractor-trailer combination that is equipped with air brakes. For the purpose of this subsection, gross vehicle weight rating, or GVWR, means the value specified by the manufacturer as the loaded weight of the tow truck.
 - Is equipped with flashing, rotating, or (B) oscillating amber lights, visible for at least 500 feet in all directions.
 - (C) Is capable of utilizing the lighting and braking systems of the disabled vehicle or combination of vehicles.
 - (D) Does not engage a tow exceeding 50 highway miles from the initial point of wreck or disablement to a place of repair. Any additional movement of the vehicles may occur only upon issuance of authorization

for that movement under the provisions of Sections
15-301 through 15-318 of this Code.
The Department may by rule or regulation prescribe

additional requirements regarding length limitations for a tow truck towing another vehicle.

For purposes of this Section, a tow-dolly that merely serves as substitute wheels for another legally licensed vehicle is considered part of the licensed vehicle and not a separate vehicle.

- (7) Commercial vehicles consisting of 3 vehicles, provided the following:
 - (A) The total overall dimension does not exceed 65 feet.
 - (B) The towing vehicle is a properly registered vehicle capable of towing another vehicle using a fifth-wheel type assembly or a goose-neck hitch ball.
 - (C) The third vehicle must be the lightest of the 3 vehicles and be a trailer or semitrailer.
 - (D) All vehicles must be properly equipped with operating brakes and safety equipment required by this Code.
 - (E) The combination of vehicles must be operated by a person who holds a commercial driver's license (CDL).
 - (F) The combination of vehicles must be en route to a location where new or used trailers are sold by an

25

26

1	Illinois or out-of-state licensed new or used trailer
2	dealer.
3	(c-1) A combination of 3 vehicles is allowed access to any
4	State designated highway if:
5	(1) the length of neither towed vehicle exceeds 28.5
6	feet;
7	(2) the overall wheel base of the combination of
8	vehicles does not exceed 62 feet; and
9	(3) the combination of vehicles is en route to a
10	location where new or used trailers are sold by an
11	Illinois or out-of-state licensed new or used trailer
12	dealer.
13	(c-2) A combination of 3 vehicles is allowed access from
14	any State designated highway onto any county, township, or
15	municipal highway for a distance of 5 highway miles for the
16	purpose of delivery or collection of one or both of the towed
17	vehicles if:
18	(1) the length of neither towed vehicle exceeds 28.5
19	feet;
20	(2) the combination of vehicles does not exceed 40,000
21	pounds in gross weight and 8 feet 6 inches in width;
22	(3) there is no sign prohibiting that access;
23	(4) the route is not being used as a thoroughfare

between State designated highways; and

(5) the combination of vehicles is en route to a

location where new or used trailers are sold by an

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

- Illinois or out-of-state licensed new or used trailer 1 2 dealer.
- (d) On Class I highways there are no overall length 3 limitations on motor vehicles operating in combinations 5 provided:
 - (1) The length of a semitrailer, unladen or with load, in combination with a truck tractor may not exceed 53 feet.
 - (2) The distance between the kingpin and the center of the rear axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 45 feet 6 inches. The limit contained in this paragraph (2) shall not apply to trailers or semi-trailers used for the transport of livestock as defined by Section 18b-101.
 - (3) The length of a semitrailer or trailer, unladen or with load, operated in a truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination, may not exceed 28 feet 6 inches.
 - (4) Maxi-cube combinations, as defined in Chapter 1, may not exceed 65 feet overall dimension.
 - (5) Combinations of vehicles specifically designed to transport motor vehicles or boats may not exceed 65 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.

- (6) Stinger-steered semitrailer vehicles specifically designed to transport motor vehicles or boats and automobile transporters, as defined in Chapter 1, may not exceed 80 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
 - (7) A truck in transit transporting 3 trucks coupled together by the triple saddlemount method may not exceed 97 feet overall dimension.
- (8) A towaway trailer transporter combination may not exceed 82 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismantled or disassembled are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided

- that during night operations every vehicle and its load must 1
- 2 be equipped with a sufficient number of clearance lamps on
- 3 both sides and marker lamps on the extreme ends of any
- projecting load to clearly mark the dimensions of the load. 4
- A tow truck in combination with a disabled vehicle or
- combination of disabled vehicles, as provided in paragraph (6) 6
- of subsection (c) of this Section, is exempt from length 7
- 8 limitations.
- 9 The length limitations described in this paragraph (d)
- 10 shall be exclusive of safety and energy conservation devices,
- 11 such as bumpers, refrigeration units or air compressors and
- 12 other devices, that the Department may interpret as necessary
- 13 for safe and efficient operation; except that no device
- 14 excluded under this paragraph shall have by its design or use
- 15 the capability to carry cargo.
- 16 Section 5-35 of the Illinois Administrative Procedure Act
- 17 relating to procedures for rulemaking shall not apply to the
- designation of highways under this paragraph (d). 18
- 19 (e) On Class II highways there are no overall length
- 20 limitations on motor vehicles operating in combinations,
- 21 provided:
- 22 (1) The length of a semitrailer, unladen or with load,
- 23 in combination with a truck tractor, may not exceed 53
- feet overall dimension. 24
- 25 (2) The distance between the kingpin and the center of
- 26 the rear axle of a semitrailer longer than 48 feet, in

- (3) A truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination may not exceed 65 feet in dimension from front axle to rear axle.
- (4) The length of a semitrailer or trailer, unladen or with load, operated in a truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer combination, may not exceed 28 feet 6 inches.
- (5) Maxi-cube combinations, as defined in Chapter 1, may not exceed 65 feet overall dimension.
- (6) A combination of vehicles, specifically designed to transport motor vehicles or boats, may not exceed 65 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
- (7) Stinger-steered semitrailer vehicles specifically designed to transport motor vehicles or boats may not exceed 80 feet overall dimension. The length limitation is inclusive of front and rear bumpers but exclusive of the overhang of the transported vehicles, as provided in paragraph (i) of this Section.
 - (8) A truck in transit transporting 3 trucks coupled

together by the triple saddlemount method may not exceed

97 feet overall dimension.

(9) A towaway trailer transporter combination may not exceed 82 feet overall dimension.

Vehicles operating during daylight hours when transporting poles, pipes, machinery, or other objects of a structural nature that cannot readily be dismantled or disassembled are exempt from length limitations, provided that no object may exceed 80 feet in length and the overall dimension of the vehicle including the load may not exceed 100 feet. This exemption does not apply to operation on a Saturday, Sunday, or legal holiday. Legal holidays referred to in this Section are the days on which the following traditional holidays are celebrated: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties are exempt from length limitations, provided that during night operations every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps on the extreme ends of any projecting load to clearly mark the dimensions of the load.

A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

Local authorities, with respect to streets and highways under their jurisdiction, may also by ordinance or resolution allow length limitations of this subsection (e).

The length limitations described in this paragraph (e) shall be exclusive of safety and energy conservation devices, such as bumpers, refrigeration units or air compressors and other devices, that the Department may interpret as necessary for safe and efficient operation; except that no device excluded under this paragraph shall have by its design or use the capability to carry cargo.

Section 5-35 of the Illinois Administrative Procedure Act relating to procedures for rulemaking shall not apply to the designation of highways under this paragraph (e).

- (e-1) (Blank).
- (e-2) Except as provided in subsection (e-3), combinations of vehicles over 65 feet in length, with no overall length limitation except as provided in subsections (d) and (e) of this Section, are allowed access as follows:
 - (1) From a Class I highway onto any street or highway for a distance of one highway mile for the purpose of loading, unloading, food, fuel, repairs, and rest, provided there is no sign prohibiting that access.
 - (2) From a Class I or Class II highway onto any non-designated highway for a distance of 5 highway miles for the purpose of loading, unloading, food, fuel, repairs, and rest if:

- 1 (A) there is no sign prohibiting that access; and
- 2 (B) the route is not being used as a thoroughfare between Class I or Class II highways.
 - (e-3) Combinations of vehicles over 65 feet in length operated by household goods carriers or towaway trailer transporter combinations, with no overall length limitations except as provided in subsections (d) and (e) of this Section, have unlimited access to points of loading, unloading, or delivery to or from a manufacturer, distributor, or dealer.
 - (f) On non-designated highways, the maximum length limitations for vehicles in combination are as follows:
 - (1) A truck tractor in combination with a semitrailer may not exceed 65 feet overall dimension. An agency or instrumentality of the State or any unit of local government shall not be required to design or construct a new non designated highway or to widen or otherwise alter a non designated highway to accommodate truck tractor semitrailer combinations under this paragraph (1).
 - (2) Semitrailers, unladen or with load, may not exceed 53 feet overall dimension.
 - (3) A truck tractor-semitrailer-trailer or truck tractor semitrailer-semitrailer may not exceed 60 feet overall dimension.
 - (4) The distance between the kingpin and the center axle of a semitrailer longer than 48 feet, in combination with a truck tractor, may not exceed 42 feet 6 inches. The

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

limit contained in this paragraph (4) shall not apply to 1 2 trailers or semi-trailers used for the transport of 3 livestock as defined by Section 18b-101.

An agency or instrumentality of the State or any unit of local government shall not be required to design, construct, alter, widen, or maintain any non-designated highway to accommodate vehicles in combination under this subsection (f). For the purposes of designing or modifying the intersection of a local roadway and a State roadway that does not accommodate vehicles under this subsection (f), a local unit of government may request in writing for the Department to restrict the length of vehicles turning on to or off of any jurisdiction roadway of the intersection. The Department may, in its sole discretion, restrict the length of vehicles turning on to or off of any jurisdiction roadway of the intersection. A restriction so determined and declared by the Department becomes effective, when appropriate signs giving notice of the limit are erected. Each governmental entity shall cause signage to be installed on its respective roadway to notify vehicles of turning and length restrictions. Vehicles that exceed posted measurements shall be prohibited from turning to access the roadway.

- (g) Length limitations in the preceding subsections of this Section 15-107 do not apply to the following:
- (1) Vehicles operated in the daytime, except on Saturdays, Sundays, or legal holidays, when transporting

poles, pipe, machinery, or other objects of a structural nature that cannot readily be dismantled or disassembled, provided the overall length of vehicle and load may not exceed 100 feet and no object exceeding 80 feet in length may be transported unless a permit has been obtained as authorized in Section 15-301. As used in this Section, "legal holiday" means any of the following days: New Year's Day; Memorial Day; Independence Day; Labor Day; Thanksgiving Day; and Christmas Day.

- (2) Vehicles and loads operated by a public utility while en route to make emergency repairs to public service facilities or properties, but during night operation every vehicle and its load must be equipped with a sufficient number of clearance lamps on both sides and marker lamps upon the extreme ends of any projecting load to clearly mark the dimensions of the load.
- (3) A tow truck in combination with a disabled vehicle or combination of disabled vehicles, as provided in paragraph (6) of subsection (c) of this Section, is exempt from length limitations.

The towing vehicle, however, may tow any disabled vehicle from the initial point of wreck or disablement to a point where repairs are actually to occur. This movement shall be valid only on State routes. The tower must abide by posted bridge weight limits.

All other combinations not listed in this subsection (f)

3

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

1 may not exceed 60 feet overall dimension.

- (h) The load upon any vehicle operated alone, or the load upon the front vehicle of a combination of vehicles, shall not extend more than 3 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a front bumper. The provisions of this subsection (h) shall not apply to any vehicle or combination of vehicles specifically designed for the collection and transportation of waste, vehicle's recyclable materials during the garbage, or operation in the course of collecting garbage, waste, or recyclable materials if the vehicle is traveling at a speed not in excess of 15 miles per hour during the vehicle's operation and in the course of collecting garbage, waste, or recyclable materials. However, in no instance shall the load extend more than 7 feet beyond the front wheels of the vehicle or the front bumper of the vehicle if it is equipped with a front bumper.
- (i) The load upon the front vehicle of an automobile transporter or a stinger-steered vehicle specifically designed to transport motor vehicles shall not extend more than 4 feet beyond the foremost part of the transporting vehicle and the load upon the rear transporting vehicle shall not extend more than 6 feet beyond the rear of the bed or body of the vehicle. This paragraph shall only be applicable upon highways designated in paragraphs (d) and (e) of this Section.
 - (j) Articulated vehicles comprised of 2 sections, neither

- of which exceeds a length of 42 feet, designed for the carrying
- of more than 10 persons, may be up to 60 feet in length, not
- 3 including energy absorbing bumpers, provided that the vehicles
- 4 are:
- 5 1. operated by or for any public body or motor carrier
- 6 authorized by law to provide public transportation
- 7 services; or
- 8 2. operated in local public transportation service by
- 9 any other person and the municipality in which the service
- is to be provided approved the operation of the vehicle.
- 11 $(\dot{j}-1)$ (Blank).
- 12 (k) Any person who is convicted of violating this Section
- is subject to the penalty as provided in paragraph (b) of
- 14 Section 15-113.
- 15 (l) (Blank).
- 16 (Source: P.A. 102-124, eff. 7-23-21; 103-258, eff. 1-1-24.)
- 17 (625 ILCS 5/15-116)
- 18 Sec. 15-116. Highway designations.
- 19 (a) The Department of Transportation shall maintain and
- 20 provide a listing of all Class I and Class II designated
- 21 streets and highways as defined in Chapter 1 of this Code.
- 22 (b) The Department shall also maintain and provide a
- 23 listing of all local streets or highways that have been
- designated Class II by local agencies.
- 25 (c) Local agencies shall be responsible for reporting to

- 1 the Department all streets and highways under their
- 2 jurisdiction designated Class II. Local agencies shall also
- 3 provide to the Department reference contact names and
- 4 telephone numbers.
- 5 (d) The Department shall also maintain and provide an
- 6 official map of the Designated State Truck Route System that
- 7 includes State and local streets and highways that have been
- 8 designated Class I or Class II.
- 9 (e) If a unit of local government has no Class II
- 10 designated truck routes, the unit of local government shall
- 11 affirm to the Department that it has no such truck routes.
- 12 (f) Each unit of local government shall report to the
- 13 Department, and the Department shall post on its official
- 14 website, any limitations prohibiting the operation of vehicles
- 15 imposed by ordinance or resolution in the unit of local
- 16 government's non-designated highway system and any
- 17 non-designated highway that is not designed and constructed
- after January 1, 2024 2023 to the overall length dimension of
- 19 vehicles permitted under paragraph (1) of subsection (f) of
- 20 Section 15-107.
- 21 (Source: P.A. 103-258, eff. 1-1-24.)